

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Part No. 124226  
Printing date 01/05/2011

Revised On 01/05/2011

## 1 Identification of the substance and manufacturer

**Trade name:** NEW CEILING WHITE  
**Product code:** 0000200051  
**Manufacturer/Supplier:** SEYMOUR OF SYCAMORE  
917 Crosby Avenue  
Sycamore, IL 60178  
(815)-895-9101, www.seymourpaint.com



**Emergency telephone number:** CHEMTEL 1-800-255-3924, 813-248-0585 \*if located outside the U.S.\*

## 2 Composition/information on ingredients

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

### Dangerous components:

74-98-6	propane	18.95%
108-88-3	Toluene	13.89%
106-97-8	n-butane	11.13%
13463-67-7	titanium dioxide	9.66%
64742-89-8	VM&P Naphtha	6.73%
1317-65-3	Calcium Carbonate	5.4%
64742-47-8	Mineral Spirits	2.51%
1330-20-7	xylene (mix)	1.87%
108-65-6	PM acetate	1.47%

## 3 Hazards identification

**Hazard Information:** Extremely flammable liquid and vapor. Keep away from heat, sparks, and flame.  
Has narcotizing effect.

**Risk phrases:** Extremely flammable.  
Irritating to respiratory system and skin.  
Harmful: danger of serious damage to health by prolonged exposure through inhalation.

**Safety phrases:** Keep out of the reach of children.  
Keep away from sources of ignition - No smoking.  
Do not breathe gas/fumes/vapour/spray.  
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point  
Wear suitable protective clothing and gloves.  
If swallowed, seek medical advice immediately and show this container or label.  
Use only in well-ventilated areas.

**Special precautions:** Do not spray on a naked flame or any incandescent material.

**Effects of chronic overexposure:** Buildup of explosive mixtures possible without sufficient ventilation.  
May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

**NFPA ratings (0 - 4):**  
Health- 1  
Flammability- 3  
Reactivity- 3

**HMS-ratings (0 - 4):**  
Health- 1  
Flammability- 3  
Physical Hazard- 3

## 4 First aid measures

**After inhalation:** Supply fresh air; consult doctor in case of complaints.  
**After skin contact:** Remove contaminated clothing. Wash exposed area with soap and water.  
**After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.  
**After swallowing:** Contact physician or poison control center.

## 5 Firefighting measures

**Extinguishing agents:** CO2, sand, extinguishing powder, or water spray.  
**Special hazards:** No further relevant information available.  
**Protective equipment:** No special measures required.

## 6 Accidental release measures

**Personal safety procedures:** Wear protective equipment. Keep unprotected persons away.  
**Environmental precautions:** Do not allow product to reach sewage systems or ground water.  
**Additional precautions:** Ensure adequate ventilation.

## 7 Handling and storage

**Fire/explosion protection:** Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges.  
**Storage requirements:** Observe pressurized container storage regulations. Consult with your local authorities.

## 8 Exposure controls/personal protection

### Components with limit values that require monitoring at the workplace:

74-98-6 propane	
PEL	1800 mg/m <sup>3</sup> , 1000 ppm
REL	1800 mg/m <sup>3</sup> , 1000 ppm
TLV	Varies mg/m <sup>3</sup> , 1000 ppm

(Contd. on page 2)  
USA

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/05/2011

Revised On 01/05/2011

Trade name: NEW CEILING WHITE

(Contd. of page 1)

**108-88-3 Toluene**

PEL	Short-term value: C 300; 500* ppm Long-term value: 200 ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm Long-term value: 375 mg/m <sup>3</sup> , 100 ppm
TLV	75 mg/m <sup>3</sup> , 20 ppm NIC-BEI

**106-97-8 n-butane**

REL	1900 mg/m <sup>3</sup> , 800 ppm
TLV	Varies mg/m <sup>3</sup> , 1000 ppm

**1330-20-7 xylene (mix)**

PEL	435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI

**108-65-6 PM acetate**

WEEL	50 ppm
------	--------

<b>Hygienic protection:</b>	Keep away from foodstuffs and animal feed. Wash hands after use.
<b>Breathing equipment:</b>	A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.
<b>Hand protection:</b>	Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove recommendation can be given.
<b>Eye protection:</b>	Tightly sealed goggles

**9 Physical and chemical properties**

<b>Odor:</b>	Aromatic
<b>pH-value:</b>	Not determined.
<b>Boiling point:</b>	-44°C (-47°F)
<b>Flash point:</b>	-19°C (-2°F)
<b>Auto igniting:</b>	Product is not self-igniting.
<b>Danger of explosion:</b>	Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture.
<b>Lower Explosion Limit:</b>	1.5 Vol %
<b>Upper Explosion Limit:</b>	10.9 Vol %
<b>Vapor Pressure:</b>	40 PSI, 2750 hPa
<b>Specific Gravity:</b>	Between 0.77 and 0.85 (Water equals 1.00)
<b>VOC content:</b>	575.7 g/l / 4.80 lb/gl
<b>VOC content (less exempt solvents):</b>	57.0 %
<b>Water:</b>	21.3 %
<b>MIR Value:</b>	1.13
<b>Solids content:</b>	21.7 %
<b>Other information</b>	No further relevant information available.

**10 Stability and reactivity**

<b>Conditions to avoid:</b>	Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.
<b>Hazardous reactions:</b>	No dangerous reactions known.
<b>Hazardous decomposition:</b>	No dangerous decomposition products known.

**11 Toxicological information**

<b>Skin effects:</b>	No irritant effect.
<b>Eye effects:</b>	No irritating effect.
<b>Sensitization:</b>	No sensitizing effects known.

**12 Ecological information**

<b>Aquatic toxicity:</b>	Hazardous for water, do not empty into drains.
<b>Other information:</b>	This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), or chlorinated solvents.

**13 Disposal considerations**

<b>DISPOSAL METHOD:</b>	Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
<b>Recommendation:</b>	Completely empty cans should be recycled.

**14 Transport information**

<b>Hazard class:</b>	2.1
<b>Identification number:</b>	N/A
<b>Label</b>	2.1
<b>ADR/RID/TDG class:</b>	2 5F Gases
<b>UN-Number:</b>	1950
<b>IMDG Class:</b>	2.1

(Contd. on page 3)  
USA

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/05/2011

Revised On 01/05/2011

Trade name: NEW CEILING WHITE

(Contd. of page 2)

**Packaging group:** II  
**EMS Number:** F-D,S-U  
**Marine pollutant:** No  
**ICAO/IATA Class:** 2.1  
**Special marking:** Consumer Commodity ORM-D

## 15 Regulatory information

**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

**SARA Section 313 (Specific toxic chemical listings):**

108-88-3	Toluene
1330-20-7	xylene (mix)

**TSCA:** All ingredients are listed.  
**CPSC:** This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

**California Proposition 65 chemicals known to cause cancer:**

100-41-4	ethyl benzene
----------	---------------

**California Proposition 65  
chemicals known to cause  
developmental toxicity:  
CANADIAN ENVIRONMENTAL  
PROTECTION ACT:  
WHMIS Symbols for Canada:**

108-88-3 Toluene

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.  
 A - Compressed gas  
 D2A - Very toxic material causing other toxic effects



**EPA:** A= Known human carcinogen      B= Probable human carcinogen  
 C= Possible human carcinogen  
 D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence of carcinogenicity (or no data is available).  
 I: 'Data are inadequate for an assessment of human carcinogeni potential.'  
 II: 'Inadequate information to assess carcinogenic potential.'

108-88-3	Toluene	II
1330-20-7	xylene (mix)	I

**IARC:** Group 2A: The ingredient is probably carcinogenic to humans.  
 Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence of carcinogenicity.  
 Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.

108-88-3	Toluene	3
13463-67-7	titanium dioxide	2B
1330-20-7	xylene (mix)	3

**ACGIH:** A1-designates a confirmed human carcinogen.  
 A2-designates a suspected human carcinogen.  
 A3-designates an animal carcinogen.  
 A4-designates "not classifiable as a human carcinogen".

108-88-3	Toluene	A4
13463-67-7	titanium dioxide	A4
1330-20-7	xylene (mix)	A4

**NIOSH:** The following substances are regulated in the United States with reference to occupational exposure limits:

13463-67-7	titanium dioxide
------------	------------------

**Hazard symbols:**


Harmful  
Extremely flammable

## 16 Other information

This product was manufactured in the U.S.A.

The information on this sheet is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Contact:** Regulatory Affairs

**Abbreviations and acronyms:**

GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 VOC: Volatile Organic Compounds (USA, EU)  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 HMIS: Hazardous Materials Identification System (USA)  
 ISO: International Organization for Standardization  
 EPA: Environmental Protection Agency  
 IARC: International Agency for the Research of Cancer  
 NIOSH: National Institute for Occupational Safety and Health  
 TSCA: Toxic Substances Control Act  
 CPSC: Consumer Product Safety Commission