

4. FIRST AID MEASURES Eyes: Flush with water for 15 minutes. Call a physician.

Ingestion: Get medical attention immediately.

Special protective equipment when fighting fire: none.

Cleaning measures: Remove spoiled product mechanically.

Store in a dry place in closed packages.

- **Respiratory protection:** use an air purifying dust respirator.
- **Hands protection:** wear appropriate gloves to prevent skin contact.
- **Eyes protection:** welder's helmets.
- **Skin protection:** wear appropriate overalls to prevent skin or body contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: solid.

Odor: none

pH : non applicable

Melting point: 1560-2000° F, 850-1100° C

Relative density: 6-9 g/cm³

Solubility: insoluble in water

10. STABILITY AND REACTIVITY

STABILITY

Conditions to avoid: not applicable.

Materials to avoid: reacts with acids.

Hazardous decomposition products: unknown.

11. TOXICOLOGICAL INFORMATION

Effects of acute exposure

Toxicity to animals: unknown

Local effects: not applicable.

Inhalation: not applicable for the product. For welding fumes see section 3.

Ingestion: not applicable.

Contact with skin: no adverse effects expected.

CARCINOGENICITY:

16.

Material Safety Data Sheet

Harpoon
Part No. 818195 5/32"

MSDS # 405
Latest Revision: January 2011
Page 5 of 5
Sosmetal Products, Inc.

The information in this document is believed to be correct as of the date issued. However, no warranty is expressed to be implied regarding the accuracy or completeness of this information. This information and product are furnished on the condition that the person receiving them shall make his own determinations as to the suitability of the product for his particular purpose and on the condition that he assumes the risk of his use thereof.

This Material Safety Data Sheet complies with the EC directives 91/155/EEC and 93/112/EEC Including modifications 2001/58/EC.

Complies with OSHA Communication Standard 29 CFR 1910.1200 and Superfund Amendments and Reauthorization Act (SARA) of 1986 Public Law 99-499

End of the document.